

MUNICIPAL CODE OF THE CITY OF NEW HAVEN

CHAPTER 415: FLOODPLAIN MANAGEMENT

ARTICLE I. STATUTORY AUTHORIZATION, FINDINGS OF FACT AND PURPOSES

SECTION 415.010: STATUTORY AUTHORIZATION

The legislature of the State of Missouri has in Chapter 89, RSMo., delegated the responsibility to local governmental units to adopt floodplain management regulations designed to protect the health, safety and general welfare. Therefore, the Board of Aldermen of the City of New Haven, Missouri, ordains as follows. (Ord. No. 819 Art. 1 §A, 4-12-05)

SECTION 415.020: FINDINGS OF FACT

- A. *Flood Losses Resulting From Periodic Inundation.* The special flood hazard areas of New Haven, Missouri, are subject to inundation which results in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base; all of which adversely affect the public health, safety and general welfare.
- B. *General Causes Of The Flood Losses.* These flood losses are caused by:
1. The cumulative effect of development in any delineated floodplain causing increases in flood heights and velocities; and
 2. The occupancy of flood hazard areas by uses vulnerable to floods, hazardous to others, inadequately elevated or otherwise unprotected from flood damages.
- C. *Methods Used To Analyze Flood Hazards.* The Flood Insurance Study (FIS) that is the basis of this Chapter uses a standard engineering method of analyzing flood hazards which consist of a series of interrelated steps.
1. Selection of a base flood that is based upon engineering calculations which permit a consideration of such flood factors as its expected frequency of occurrence, the area inundated and the depth of inundation. The base flood selected for this Chapter is representative of large floods which are characteristic of what can be expected to occur on the particular streams subject to this Chapter. It is in the general order of a flood which could be expected to have a one percent (1%) chance of occurrence in any one (1) year as delineated on the Federal Insurance Administrator's FIS and illustrative materials dated February 18, 1981, as amended, and any future revisions thereto.
 2. Calculation of water surface profiles are based on a standard hydraulic engineering analysis of the capacity of the stream channel and overbank areas to convey the regulatory flood.
 3. Computation of a floodway required to convey this flood without increasing flood

heights more than one (1) foot at any point.

4. Delineation of floodway encroachment lines within which no development is permitted that would cause any increase in flood height.
5. Delineation of flood fringe, i.e., that area outside the floodway encroachment lines but still subject to inundation by the base flood. (Ord. No. 819 Art. 1 §B, 4-12-05)

SECTION 415.030: STATEMENT OF PURPOSE

It is the purpose of this Chapter to promote the public health, safety and general welfare; to minimize those losses described in Article I, Section 415.020(A); to establish or maintain the community's eligibility for participation in the National Flood Insurance Program (NFIP) as defined in 44 Code of Federal Regulations (CFR) 59.22(a)(3); and to meet the requirements of 44 CFR 60.3(d) by applying the provisions of this Chapter to:

1. Restrict or prohibit uses that are dangerous to health, safety or property in times of flooding or cause undue increases in flood heights or velocities;
2. Require uses vulnerable to floods, including public facilities that serve such uses, be provided with flood protection at the time of initial construction; and
3. Protect individuals from buying lands that are unsuited for the intended development purposes due to the flood hazard. (Ord. No. 819 Art. 1 §C, 4-12-05)

ARTICLE II. GENERAL PROVISIONS

SECTION 415.040: LANDS TO WHICH CHAPTER APPLIES

This Chapter shall apply to all lands within the jurisdiction of the City of New Haven, Missouri, identified as numbered and unnumbered A Zones and AE Zones on the Flood Insurance Rate Map (FIRM) and Flood Boundary and Floodway Map (FBFM) dated February 18, 1981, as amended, and any future revisions thereto. In all areas covered by this Chapter, no development shall be permitted except through the issuance of a floodplain development permit granted by the Board of Aldermen or its duly designated representative under such safeguards and restrictions as the Board of Aldermen or the designated representative may reasonably impose for the promotion and maintenance of the general welfare, health of the inhabitants of the community and as specifically noted in Article IV. (Ord. No. 819 Art. 2 §A, 4-12-05)

SECTION 415.050: FLOODPLAIN ADMINISTRATOR

Mr. John Neff, Building Inspector, is hereby designated as the Floodplain Administrator under this Chapter. (Ord. No. 819 Art. 2 §B, 4-12-05)

SECTION 415.060: COMPLIANCE

No development located within the special flood hazard areas of this community shall be located, extended, converted or structurally altered without full compliance with the terms of this Chapter and other applicable regulations. (Ord. No. 819 Art. 2 §C, 4-12-05)

SECTION 415.070: ABROGATION AND GREATER RESTRICTIONS

It is not intended by this Chapter to repeal, abrogate or impair any existing easements, covenants or deed restrictions. However, where this Chapter imposes greater restrictions, the provisions of this Chapter shall prevail. All other Chapters inconsistent with this Chapter are hereby repealed to the extent of the inconsistency only. (Ord. No. 819 Art. 2 §D, 4-12-05)

SECTION 415.080: INTERPRETATION

In their interpretation and application, the provisions of this Chapter shall be held to be minimum requirements, shall be liberally construed in favor of the Governing Body and shall not be deemed a limitation or repeal of any other powers granted by State Statutes. (Ord. No. 819 Art. 2 §E, 4-12-05)

SECTION 415.090: WARNING AND DISCLAIMER OF LIABILITY

The degree of flood protection required by this Chapter is considered reasonable for regulatory purposes and is based on engineering and scientific methods of study. Larger floods may occur on rare occasions or the flood heights may be increased by manmade or natural causes such as ice jams and bridge openings restricted by debris. This Chapter does not imply that areas outside the floodway and flood fringe or land uses permitted within such areas will be free from flooding or flood damage. This Chapter shall not create a liability on the part of the City of New Haven, any officer or employee thereof, for any flood damages that may result from reliance on this Chapter or any administrative decision lawfully made thereunder. (Ord. No. 819 Art. 2 §F, 4-12-05)

SECTION 415.100: SEVERABILITY

If any Section, clause, provision or portion of this Chapter is adjudged unconstitutional or invalid by a court of appropriate jurisdiction, the remainder of this Chapter shall not be affected thereby. (Ord. No. 819 Art. 2 §G, 4-12-05)

ARTICLE III. ADMINISTRATION

SECTION 415.110: FLOODPLAIN DEVELOPMENT PERMIT

A floodplain development permit shall be required for all proposed construction or other development, including the placement of manufactured homes, in the areas described in Article II, Section 415.040. No person, firm, corporation or unit of government shall initiate any development or substantial improvement or cause the same to be done without first

obtaining a separate floodplain development permit for each structure or other development. (Ord. No. 819 Art. 3 §A, 4-12-05)

SECTION 415.120: DESIGNATION OF FLOODPLAIN ADMINISTRATOR

Mr. John Neff, Building Inspector, is hereby appointed to administer and implement the provisions of this Chapter. (Ord. No. 819 Art. 3 §B, 4-12-05)

SECTION 415.130: DUTIES AND RESPONSIBILITIES OF FLOODPLAIN ADMINISTRATOR

Duties of the Floodplain Administrator shall include, but not be limited to:

1. Review of all applications for floodplain development permits to assure that sites are reasonably safe from flooding and that the floodplain development permit requirements of this Chapter have been satisfied;
2. Review of all applications for floodplain development permits for proposed development to assure that all necessary permits have been obtained from Federal, State or local governmental agencies from which prior approval is required by Federal, State or local law;
3. Review all subdivision proposals and other proposed new development, including manufactured home parks or subdivisions, to determine whether such proposals will be reasonably safe from flooding;
4. Issue floodplain development permits for all approved applications;
5. Notify adjacent communities and the State Emergency Management Agency prior to any alteration or relocation of a watercourse and submit evidence of such notification to the Federal Emergency Management Agency (FEMA);
6. Assure that the flood-carrying capacity is not diminished and shall be maintained within the altered or relocated portion of any watercourse;
7. Verify and maintain a record of the actual elevation (in relation to mean sea level) of the lowest floor, including basement, of all new or substantially improved structures;
8. Verify and maintain a record of the actual elevation (in relation to mean sea level) that the new or substantially improved non-residential structures have been floodproofed;
9. When floodproofing techniques are utilized for a particular non-residential structure, the Floodplain Administrator shall require certification from a registered professional engineer or architect. (Ord. No. 819 Art. 3 §C, 4-12-05)

SECTION 415.140: APPLICATION FOR FLOODPLAIN DEVELOPMENT PERMIT

To obtain a floodplain development permit, the applicant shall first file an application in

writing on a form furnished for that purpose. Every floodplain development permit application shall:

1. Describe the land on which the proposed work is to be done by lot, block and tract, house and street address or similar description that will readily identify and specifically locate the proposed structure or work;
2. Identify and describe the work to be covered by the floodplain development permit;
3. Indicate the use or occupancy for which the proposed work is intended;
4. Indicate the assessed value of the structure and the fair market value of the improvement;
5. Specify whether development is located in designated flood fringe or floodway;
6. Identify the existing base flood elevation and the elevation of the proposed development;
7. Give such other information as reasonably may be required by the Floodplain Administrator;
8. Be accompanied by plans and specifications for proposed construction; and
9. Be signed by the permittee or his/her authorized agent who may be required to submit evidence to indicate such authority. (Ord. No. 819 Art. 3 §D, 4-12-05)

ARTICLE IV. PROVISIONS FOR FLOOD HAZARD REDUCTION

SECTION 415.150: GENERAL STANDARDS

- A. No permit for floodplain development shall be granted for new construction, substantial improvements and other improvements, including the placement of manufactured homes, within any numbered or unnumbered A Zones and AE Zones, unless the conditions of this Section are satisfied.
- B. All areas identified as unnumbered A Zones on the FIRM are subject to inundation of the 100-year flood; however, the base flood elevation is not provided. Development within unnumbered A Zones is subject to all provisions of this Chapter. If Flood Insurance Study data is not available, the community shall obtain, review and reasonably utilize any base flood elevation or floodway data currently available from Federal, State or other sources.
- C. Until a floodway is designated, no new construction, substantial improvements or other development, including fill, shall be permitted within any numbered A Zone or AE Zone on the FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one (1) foot at any point within the community.

D. All new construction, subdivision proposals, substantial improvements, prefabricated structures, placement of manufactured homes and other developments shall require:

1. Design or adequate anchorage to prevent flotation, collapse or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy;
2. Construction with materials resistant to flood damage;
3. Utilization of methods and practices that minimize flood damages;
4. All electrical, heating, ventilation, plumbing, air-conditioning equipment and other service facilities be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding;
5. New or replacement water supply systems and/or sanitary sewage systems be designed to minimize or eliminate infiltration of floodwaters into the systems and discharges from the systems into floodwaters and on-site waste disposal systems be located so as to avoid impairment or contamination; and
6. Subdivision proposals and other proposed new development, including manufactured home parks or subdivisions, located within special flood hazard areas are required to assure that:
 - a. All such proposals are consistent with the need to minimize flood damage;
 - b. All public utilities and facilities, such as sewer, gas, electrical and water systems, are located and constructed to minimize or eliminate flood damage;
 - c. Adequate drainage is provided so as to reduce exposure to flood hazards; and
 - d. All proposals for development, including proposals for manufactured home parks and subdivisions, of five (5) acres or fifty (50) lots, whichever is lesser, include within such proposals base flood elevation data.

E. *Storage, Material And Equipment.*

1. The storage or processing of materials within the special flood hazard area that are in time of flooding buoyant, flammable, explosive or could be injurious to human, animal or plant life is prohibited.
2. Storage of other material or equipment may be allowed if not subject to major damage by floods, if firmly anchored to prevent flotation, or if readily removable from the area within the time available after a flood warning.

F. *Agricultural Structures.* Structures used solely for agricultural purposes in connection with the production, harvesting, storage, drying or raising of agricultural commodities, including the raising of livestock, may be constructed at-grade and wet-floodproofed provided there is no human habitation or occupancy of the structure; the structure is of single-wall design; there is no permanent retail, wholesale or manufacturing use included in the structure; a variance has been granted from the floodplain management requirements of this Chapter;

and a floodplain development permit has been issued.

- G. *Accessory Structures.* Structures used solely for parking and limited storage purposes, not attached to any other structure on the site, of limited investment value and not larger than four hundred (400) square feet may be constructed at-grade and wet-floodproofed provided there is no human habitation or occupancy of the structure; the structure is of single-wall design; a variance has been granted from the standard floodplain management requirements of this Chapter; and a floodplain development permit has been issued. (Ord. No. 819 Art. 4 §A, 4-12-05)

SECTION 415.160: SPECIFIC STANDARDS

In all areas identified as numbered and unnumbered A Zones and AE Zones, where base flood elevation data have been provided as set forth in Article IV, Section 415.150(B), the following provisions are required:

1. *Residential construction.* New construction or substantial improvement of any residential structures, including manufactured homes, shall have the lowest floor, including basement, elevated to one (1) foot above base flood elevation.
2. *Non-residential construction.* New construction or substantial improvement of any commercial, industrial or other non-residential structures, including manufactured homes, shall have the lowest floor, including basement, elevated to one (1) foot above the base flood elevation or, together with attendant utility and sanitary facilities, be floodproofed so that below the base flood elevation the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. A registered professional engineer or architect shall certify that the standards of this Subsection are satisfied. Such certification shall be provided to the Floodplain Administrator as set forth in Article III, Section 415.130(9).
3. Require, for all new construction and substantial improvements, that fully enclosed areas below lowest floor used solely for parking of vehicles, building access or storage in an area other than a basement and that are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a registered professional engineer or architect or meet or exceed the following minimum criteria:
 - a. A minimum of two (2) openings having a total net area of not less than one (1) square inch for every square foot of enclosed area subject to flooding shall be provided; and
 - b. The bottom of all opening shall be no higher than one (1) foot above grade. Openings may be equipped with screens, louvers, valves or other coverings or devices provided that they permit the automatic entry and exit of floodwaters. (Ord. No. 819 Art. 4 §B, 4-12-05)

SECTION 415.170: MANUFACTURED HOMES

- A. All manufactured homes to be placed within all unnumbered and numbered A Zones and AE Zones on the community's FIRM shall be required to be installed using methods and practices that minimize flood damage. For the purposes of this requirement, manufactured homes must be elevated and anchored to resist flotation, collapse or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors.
- B. Require manufactured homes that are placed or substantially improved within unnumbered or numbered A Zones and AE Zones on the community's FIRM on sites:
1. Outside of manufactured home park or subdivision;
 2. In a new manufactured home park or subdivision;
 3. In an expansion to an existing manufactured home park or subdivision; or
 4. In an existing manufactured home park or subdivision on which a manufactured home has incurred substantial damage as the result of a flood,

be elevated on a permanent foundation such that the lowest floor of the manufactured home is elevated to one (1) foot above the base flood elevation and be securely attached to an adequately anchored foundation system to resist flotation, collapse and lateral movement.
- C. Require that manufactured homes to be placed or substantially improved on sites in an existing manufactured home park or subdivision within all unnumbered and numbered A Zones and AE Zones on the community's FIRM that are not subject to the provisions of Article IV, Section 415.170(B) of this Chapter be elevated so that either:
1. The lowest floor of the manufactured home is at or one (1) foot above the base flood level; or
 2. The manufactured home chassis is supported by reinforced piers or other foundation elements of at least equivalent strength that are no less than thirty-six (36) inches in height above grade and be securely attached to an adequately anchored foundation system to resist flotation, collapse and lateral movement. (Ord. No. 819 Art. 4 §C, 4-12-05)

SECTION 415.180: FLOODWAY

Located within areas of special flood hazard established in Article II, Section 415.040 are areas designated as floodways. Since the floodway is an extremely hazardous area due to the velocity of floodwaters that carry debris and potential projectiles, the following provisions shall apply:

1. The community shall select and adopt a regulatory floodway based on the principal that the area chosen for the regulatory floodway must be designed to carry the waters of the base flood without increasing the water surface elevation of that flood more than one (1) foot at any point.

2. The community shall prohibit any encroachments, including fill, new construction, substantial improvements and other development, within the adopted regulatory floodway unless it has been demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practice that the proposed encroachment would not result in any increase in flood levels within the community during the occurrence of the base flood discharge.
3. If Article IV, Section 415.180(2) is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of Article IV.
4. In unnumbered A Zones, the community shall obtain, review and reasonably utilize any base flood elevation or floodway data currently available from Federal, State or other sources as set forth in Article IV, Section 415.150(B). (Ord. No. 819 Art. 4 §D, 4-12-05)

SECTION 415.190: RECREATIONAL VEHICLES

Require that recreational vehicles placed on sites within all unnumbered and numbered A Zones and AE Zones on the community's FIRM either:

1. Be on the site for fewer than one hundred eighty (180) consecutive days; or
2. Be fully licensed and ready for highway use*; or
3. Meet the permitting, elevation and the anchoring requirements for manufactured homes of this Chapter.

*A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick-disconnect type utilities and security devices and has no permanently attached additions. (Ord. No. 819 Art. 4 §E, 4-12-05)

ARTICLE V. FLOODPLAIN MANAGEMENT VARIANCE PROCEDURES

SECTION 415.200: ESTABLISHMENT OF APPEAL BOARD

The Board of Adjustment as established by the Board of Aldermen shall hear and decide appeals and requests for variances from the floodplain management requirements of this Chapter. (Ord. No. 819 Art. 5 §A, 4-12-05)

SECTION 415.210: RESPONSIBILITY OF APPEAL BOARD

- A. Where an application for a floodplain development permit or request for a variance from the floodplain management regulations is denied by the Floodplain Administrator, the applicant may apply for such floodplain development permit or variance directly to the Appeal Board as defined in Article V, Section 415.200.

- B. The Board of Adjustment shall hear and decide appeals when it is alleged that there is an error in any requirement, decision or determination made by the Floodplain Administrator in the enforcement or administration of this Chapter. (Ord. No. 819 Art. 5 §B, 4-12-05)

SECTION 415.220: FURTHER APPEALS

Any person aggrieved by the decision of the Board of Adjustment or any taxpayer may appeal such decision to the Board of Aldermen as provided in the Planning and Zoning ordinances. (Ord. No. 819 Art. 5 §C, 4-12-05)

SECTION 415.230: FLOODPLAIN MANAGEMENT VARIANCE CRITERIA

In passing upon such applications for variances, the Board of Adjustment shall consider all technical data and evaluations, all relevant factors, standards specified in other Sections of this Chapter and the following criteria:

1. The danger to life and property due to flood damage;
2. The danger that materials may be swept onto other lands to the injury of others;
3. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;
4. The importance of the services provided by the proposed facility to the community;
5. The necessity to the facility of a waterfront location, where applicable;
6. The availability of alternative locations, not subject to flood damage, for the proposed use;
7. The compatibility of the proposed use with existing and anticipated development;
8. The relationship of the proposed use to the Comprehensive Plan and floodplain management program for that area;
9. The safety of access to the property in times of flood for ordinary and emergency vehicles;
10. The expected heights, velocity, duration, rate of rise and sediment transport of the floodwaters, if applicable, expected at the site; and
11. The costs of providing governmental services during and after flood conditions, including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, streets and bridges. (Ord. No. 819 Art. 5 §D, 4-12-05)

SECTION 415.240: CONDITIONS FOR APPROVING FLOODPLAIN MANAGEMENT VARIANCES

- A. Generally, variances may be issued for new construction and substantial improvements to be erected on a lot of one-half (½) acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, provided Subsections (B) through (F) below have been fully considered. As the lot size increases beyond the one-half (½) acre, the technical justification required for issuing the variance increases.
- B. Variances may be issued for the reconstruction, rehabilitation or restoration of structures listed on the National Register of Historic Places, the State inventory of historic places or local inventory of historic places upon determination provided the proposed activity will not preclude the structure's continued historic designation.
- C. Variances shall not be issued within any designated floodway if any increase in flood levels during the base flood discharge would result.
- D. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
- E. Variances shall only be issued upon:
 - 1. A showing of good and sufficient cause,
 - 2. A determination that failure to grant the variance would result in exceptional hardship to the applicant, and
 - 3. A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- F. A community shall notify the applicant in writing over the signature of a community official that:
 - 1. The issuance of a variance to construct a structure below base flood level will result in increased premium rates for flood insurance up to amounts as high as twenty-five dollars (\$25.00) for one hundred dollars (\$100.00) of insurance coverage, and
 - 2. Such construction below the base flood level increases risks to life and property. Such notification shall be maintained with the record of all variance actions as required by this Chapter. (Ord. No. 819 Art. 5 §E, 4-12-05)

SECTION 415.250: CONDITIONS FOR APPROVING VARIANCES FOR AGRICULTURAL STRUCTURES

- A. Any variance granted for an agricultural structure shall be decided individually based on a case-by-case analysis of the building's unique circumstances. Variances granted shall meet the following conditions as well as those criteria and conditions set forth in Article V, Sections 415.230 and 415.240 of this Chapter.
- B. In order to minimize flood damages during the 100-year flood and the threat to public health and safety, the following conditions shall be included for any variance issued for agricultural

structures that are constructed at-grade and wet-floodproofed.

1. All agricultural structures considered for a variance from the floodplain management regulations of this Chapter shall demonstrate that the varied structure is located in wide, expansive floodplain areas and no other alternate location outside of the special flood hazard area exists for the agricultural structure. Residential structures, such as farmhouses, cannot be considered agricultural structures.
2. Use of the varied structures must be limited to agricultural purposes in Zone A only as identified on the community's Flood Insurance Rate Map (FIRM).
3. For any new or substantially damaged agricultural structures, the exterior and interior building components and elements (i.e., foundation, wall framing, exterior and interior finishes, flooring, etc.) below the base flood elevation must be built with flood-resistant materials in accordance with Article IV, Section 415.150(D)(2) of this Chapter.
4. The agricultural structures must be adequately anchored to prevent flotation, collapse or lateral movement of the structures in accordance with Article IV, Section 415.150(D)(1) of this Chapter. All of the building's structural components must be capable of resisting specific flood-related forces including hydrostatic, buoyancy and hydrodynamic and debris impact forces.
5. Any mechanical, electrical or other utility equipment must be located above the base flood elevation or floodproofed so that they are contained within a watertight, floodproofed enclosure that is capable of resisting damage during flood conditions in accordance with Article IV, Section 415.150(D)(4) of this Chapter.
6. The agricultural structures must meet all National Flood Insurance Program (NFIP) opening requirements. The NFIP requires that enclosure or foundation walls, subject to the 100-year flood, contain openings that will permit the automatic entry and exit of floodwaters in accordance with Article IV, Section 415.160(3) of this Chapter.
7. The agricultural structures must comply with the floodplain management floodway encroachment provisions of Article IV, Section 415.180(2) of this Chapter. No variances may be issued for agricultural structures within any designated floodway, if any increase in flood levels would result during the 100-year flood.
8. Major equipment, machinery or other contents must be protected from any flood damage.
9. No disaster relief assistance under any program administered by any Federal agency shall be paid for any repair or restoration costs of the agricultural structures.
10. A community shall notify the applicant in writing over the signature of a community official that:
 - a. The issuance of a variance to construct a structure below base flood level will result in increased premium rates for flood insurance up to amounts as high as twenty-five dollars (\$25.00) for one hundred dollars (\$100.00) of insurance coverage, and

- b. Such construction below the base flood level increases risks to life and property. Such notification shall be maintained with the record of all variance actions as required by this Chapter.
11. Wet-floodproofing construction techniques must be reviewed and approved by the community and a registered professional engineer or architect prior to the issuance of any floodplain development permit for construction. (Ord. No. 819 Art. 5 §F, 4-12-05)

SECTION 415.260: CONDITIONS FOR APPROVING VARIANCES FOR ACCESSORY STRUCTURES

- A. Any variance granted for an accessory structure shall be decided individually based on a case-by-case analysis of the building's unique circumstances. Variances granted shall meet the following conditions as well as those criteria and conditions set forth in Article V, Sections 415.230 and 415.240 of this Chapter.
- B. In order to minimize flood damages during the 100-year flood and the threat to public health and safety, the following conditions shall be included for any variance issued for accessory structures that are constructed at-grade and wet-floodproofed.
 - 1. Use of the accessory structures must be solely for parking and limited storage purposes in Zone A only as identified on the community's Flood Insurance Rate Map (FIRM).
 - 2. For any new or substantially damaged accessory structures, the exterior and interior building components and elements (i.e., foundation, wall framing, exterior and interior finishes, flooring, etc.) below the base flood elevation must be built with flood-resistant materials in accordance with Article IV, Section 415.150(D)(2) of this Chapter.
 - 3. The accessory structures must be adequately anchored to prevent flotation, collapse or lateral movement of the structure in accordance with Article IV, Section 415.150(D)(1) of this Chapter. All of the building's structural components must be capable of resisting specific flood-related forces including hydrostatic, buoyancy and hydrodynamic and debris impact forces.
 - 4. Any mechanical, electrical or other utility equipment must be located above the base flood elevation or floodproofed so that they are contained within a watertight, floodproofed enclosure that is capable of resisting damage during flood conditions in accordance with Article IV, Section 415.150(D)(4) of this Chapter.
 - 5. The accessory structures must meet all National Flood Insurance Program (NFIP) opening requirements. The NFIP requires that enclosure or foundation walls, subject to the 100-year flood, contain openings that will permit the automatic entry and exit of floodwaters in accordance with Article IV, Section 415.160(3) of this Chapter.
 - 6. The accessory structures must comply with the floodplain management floodway encroachment provisions of Article IV, Section 415.180(2) of this Chapter. No variances may be issued for accessory structures within any designated floodway, if any increase in flood levels would result during the 100-year flood.
 - 7. Equipment, machinery or other contents must be protected from any flood damage.

8. No disaster relief assistance under any program administered by any Federal agency shall be paid for any repair or restoration costs of the accessory structures.
9. A community shall notify the applicant in writing over the signature of a community official that:
 - a. The issuance of a variance to construct a structure below base flood level will result in increased premium rates for flood insurance up to amounts as high as twenty-five dollars (\$25.00) for one hundred dollars (\$100.00) of insurance coverage, and
 - b. Such construction below the base flood level increases risks to life and property. Such notification shall be maintained with the record of all variance actions as required by this Chapter.
10. Wet-floodproofing construction techniques must be reviewed and approved by the community and registered professional engineer or architect prior to the issuance of any floodplain development permit for construction. (Ord. No. 819 Art. 5 §G, 4-12-05)

ARTICLE VI. PENALTIES FOR VIOLATION

SECTION 415.270: PENALTIES FOR VIOLATION

Violation of the provisions of this Chapter or failure to comply with any of its requirements (including violations of conditions and safeguards established in connection with granting of variances) shall constitute a misdemeanor. Any person who violates this Chapter or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than five hundred dollars (\$500.00) and, in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent the Board of Aldermen or other appropriate authority from taking such other lawful action as is necessary to prevent or remedy any violation. (Ord. No. 819 Art. 6, 4-12-05)

ARTICLE VII. AMENDMENTS

SECTION 415.280: AMENDMENTS

The regulations, restrictions and boundaries set forth in this Chapter may from time to time be amended, supplemented, changed or appealed to reflect any and all changes in the National Flood Disaster Protection Act of 1973, provided however, that no such action may be taken until after a public hearing in relation thereto, at which parties of interest and citizens shall have an opportunity to be heard. Notice of the time and place of such hearing shall be published in a newspaper of general circulation in the City of New Haven. At least twenty (20) days shall elapse between the date of this publication and the public hearing. A copy of such amendments will be provided to the Region VII office of the Federal Emergency Management Agency (FEMA). The regulations of this Chapter are in compliance with the National Flood Insurance Program (NFIP) regulations. (Ord. No. 819 Art. 7, 4-12-05)

ARTICLE VIII. DEFINITIONS

SECTION 415.290: DEFINITIONS

Unless specifically defined below, words or phrases used in this Chapter shall be interpreted so as to give them the same meaning they have in common usage and to give this Chapter its most reasonable application.

100-YEAR FLOOD: See "*BASE FLOOD*".

ACCESSORY STRUCTURE: The same as "*APPURTENANT STRUCTURE*".

ACTUARIAL RATES: See "*RISK PREMIUM RATES*".

ADMINISTRATOR: The Federal Insurance Administrator.

AGENCY: The Federal Emergency Management Agency (FEMA).

AGRICULTURAL COMMODITIES: Agricultural products and livestock.

AGRICULTURAL STRUCTURE: Any structure used exclusively in connection with the production, harvesting, storage, drying or raising of agricultural commodities.

APPEAL: A request for review of the Floodplain Administrator's interpretation of any provision of this Chapter or a request for a variance.

APPURTENANT STRUCTURE: A structure that is on the same parcel of property as the principal structure to be insured and the use of which is incidental to the use of the principal structure.

AREA OF SPECIAL FLOOD HAZARD: The land in the floodplain within a community subject to a one percent (1%) or greater chance of flooding in any given year.

BASE FLOOD: The flood having a one percent (1%) chance of being equaled or exceeded in any given year.

BASEMENT: Any area of the structure having its floor subgrade (below ground level) on all sides.

BUILDING: See "*STRUCTURE*".

CHIEF EXECUTIVE OFFICER OR CHIEF ELECTED OFFICIAL: The official of the community who is charged with the authority to implement and administer laws, ordinances and regulations for that community.

COMMUNITY: Any State or area or political subdivision thereof which has authority to adopt and enforce floodplain management regulations for the areas within its jurisdiction.

DEVELOPMENT: Any manmade change to improved or unimproved real estate including, but not limited to, buildings or other structures, levees, levee systems, mining, dredging,

filling, grading, paving, excavation or drilling operations, or storage of equipment or materials.

ELEVATED BUILDING: For insurance purposes, a non-basement building which has its lowest elevated floor raised above ground level by foundation walls, shear walls, posts, piers, pilings or columns.

ELIGIBLE COMMUNITY OR PARTICIPATING COMMUNITY: A community for which the Administrator has authorized the sale of flood insurance under the National Flood Insurance Program (NFIP).

EXISTING CONSTRUCTION: For the purposes of determining rates, structures for which the "start of construction" commenced before the effective date of the FIRM or before January 1, 1975, for FIRMs effective before that date. "Existing construction" may also be referred to as "existing structures".

EXISTING MANUFACTURED HOME PARK OR SUBDIVISION: A manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed before the effective date of the floodplain management regulations adopted by a community.

EXPANSION TO AN EXISTING MANUFACTURED HOME PARK OR SUBDIVISION: The preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).

FLOOD OR FLOODING: A general and temporary condition of partial or complete inundation of normally dry land areas from:

1. The overflow of inland and/or tidal waters, and/or
2. The unusual and rapid accumulation or runoff of surface waters from any source.

FLOOD BOUNDARY AND FLOODWAY MAP (FBFM): An official map of a community on which the Administrator has delineated both special flood hazard areas and the designated regulatory floodway.

FLOOD ELEVATION DETERMINATION: A determination by the Administrator of the water surface elevations of the base flood, that is, the flood level that has a one percent (1%) or greater chance of occurrence in any given year.

FLOOD ELEVATION STUDY: An examination, evaluation and determination of flood hazards.

FLOOD FRINGE: The area outside the floodway encroachment lines, but still subject to inundation by the regulatory flood.

FLOOD HAZARD BOUNDARY MAP (FHBM): An official map of a community, issued by the Administrator, where the boundaries of the flood areas having special flood hazards have

been designated as (unnumbered or numbered) A Zones.

FLOOD INSURANCE RATE MAP (FIRM): An official map of a community on which the Administrator has delineated both the special flood hazard areas and the risk premium zones applicable to the community.

FLOOD INSURANCE STUDY (FIS): An examination, evaluation and determination of flood hazards and, if appropriate, corresponding water surface elevations.

FLOODPLAIN OR FLOOD-PRONE AREA: Any land area susceptible to being inundated by water from any source (see "FLOODING").

FLOODPLAIN MANAGEMENT: The operation of an overall program of corrective and preventive measures for reducing flood damage including, but not limited to, emergency preparedness plans, flood control works and floodplain management regulations.

FLOODPLAIN MANAGEMENT REGULATIONS: Zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as floodplain and grading ordinances) and other applications of Police power. The term describes such state or local regulations, in any combination thereof, that provide standards for the purpose of flood damage prevention and reduction.

FLOODPROOFING: Any combination of structural and non-structural additions, changes or adjustments to structures that reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, or structures and their contents.

FLOODWAY OR REGULATORY FLOODWAY: The channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one (1) foot.

FLOODWAY ENCROACHMENT LINES: The lines marking the limits of floodways on Federal, State and local floodplain maps.

FREEBOARD: A factor of safety usually expressed in feet above a flood level for purposes of floodplain management. "Freeboard" tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as bridge openings and the hydrological effect of urbanization of the watershed.

FUNCTIONALLY DEPENDENT USE: A use that cannot perform its intended purpose unless it is located or carried out in close proximity to water. This term includes only docking facilities and facilities that are necessary for the loading and unloading of cargo or passengers, but does not include long-term storage or related manufacturing facilities.

HIGHEST ADJACENT GRADE: The highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

HISTORIC STRUCTURE: Any structure that is:

1. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior

as meeting the requirements for individual listing on the National Register;

2. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
3. Individually listed on a State inventory of historic places in States with historic preservation programs which have been approved by the Secretary of the Interior; or
4. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
 - a. By an approved State program as determined by the Secretary of the Interior, or
 - b. Directly by the Secretary of the Interior in States without approved programs.

LOWEST FLOOR: The lowest floor of the lowest enclosed area, including basement. An unfinished or flood-resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area, is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of the applicable floodproofing design requirements of this Chapter.

MANUFACTURED HOME: A structure, transportable in one (1) or more sections, that is built on a permanent chassis and is designed for use with or without a permanent foundation when attached to the required utilities. The term "*manufactured home*" does not include a "*recreational vehicle*".

MANUFACTURED HOME PARK OR SUBDIVISION: A parcel (or contiguous parcels) of land divided into two (2) or more manufactured home lots for rent or sale.

MAP: The Flood Hazard Boundary Map (FHBM), Flood Insurance Rate Map (FIRM) or the Flood Boundary and Floodway Map (FBFM) for a community issued by the Federal Emergency Management Agency (FEMA).

MARKET VALUE OR FAIR MARKET VALUE: An estimate of what is fair, economic, just and equitable value under normal local market conditions.

MEAN SEA LEVEL: For purposes of the National Flood Insurance Program (NFIP), the National Geodetic Vertical Datum (NGVD) of 1929 or other datum to which base flood elevations shown on a community's Flood Insurance Rate Map (FIRM) are referenced.

NEW CONSTRUCTION: For the purposes of determining insurance rates, structures for which the "start of construction" commenced on or after the effective date of an initial FIRM or after December 31, 1974, whichever is later, and includes any subsequent improvements to such structures. For floodplain management purposes, "*new construction*" means structures for which the "start of construction" commenced on or after the effective date of the floodplain management regulations adopted by a community and includes any subsequent improvements to such structures.

NEW MANUFACTURED HOME PARK OR SUBDIVISION: A manufactured home park or subdivision for which the construction of facilities for servicing the lot on which the

manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets and either final site grading or the pouring of concrete pads) is completed on or after the effective date of floodplain management regulations adopted by the community.

NFIP: The National Flood Insurance Program (NFIP).

PARTICIPATING COMMUNITY ALSO KNOWN AS AN ELIGIBLE COMMUNITY: A community in which the Administrator has authorized the sale of flood insurance.

PERSON: Includes any individual or group of individuals, corporation, partnership, association or any other entity, including Federal, State and local governments and agencies.

PRINCIPALLY ABOVE GROUND: That at least fifty-one percent (51%) of the actual cash value of the structure, less land value, is above ground.

RECREATIONAL VEHICLES: A vehicle which is:

1. Built on a single chassis;
2. Four hundred (400) square feet or less when measured at the largest horizontal projections;
3. Designed to be self-propelled or permanently towable by a light duty truck; and
4. Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel or seasonal use.

REMEDY A VIOLATION: To bring the structure or other development into compliance with Federal, State or local floodplain management regulations or, if this is not possible, to reduce the impacts of its non-compliance.

RISK PREMIUM RATES: Those rates established by the Administrator pursuant to individual community studies and investigations which are undertaken to provide flood insurance in accordance with Section 1307 of the National Flood Disaster Protection Act of 1973 and the accepted actuarial principals. "*Risk premium rates*" include provisions for operating costs and allowances.

SPECIAL FLOOD HAZARD AREAS: See "*AREA OF SPECIAL FLOOD HAZARD*".

SPECIAL HAZARD AREAS: An area having special flood hazards and shown on an FHBM, FIRM or FBFM as Zones (unnumbered or numbered) A and AE.

START OF CONSTRUCTION: Includes substantial improvements and means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement or other improvements were within one hundred eighty (180) days of the permit date. The "*actual start*" means either the first (1st) placement of permanent construction of a structure on a site, such as the pouring of slabs or footings, the installation of piles, the construction of columns, any work beyond the stage of excavation, or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling, the installation of streets

and/or walkways, excavation for a basement, footings, piers, foundations, the erection of temporary forms, nor installation on the property of accessory structures, such as garages or sheds, not occupied as dwelling units or not part of the main structure. For a substantial improvement, the "*actual start of construction*" means the first (1st) alteration of any wall, ceiling, floor or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

STATE COORDINATING AGENCY: That agency of the State Government or other office designated by the Governor of the State or by State Statute at the request of the Administrator to assist in the implementation of the National Flood Insurance Program (NFIP) in that State.

STRUCTURE: For floodplain management purposes, a walled and roofed building, including a gas or liquid storage tank, that is principally above ground, as well as a manufactured home. "*Structure*", for insurance purposes, means a walled and roofed building, other than a gas or liquid storage tank, that is principally above ground and affixed to a permanent site, as well as a manufactured home on a permanent foundation. For the latter purpose, the term includes a building while in the course of construction, alteration or repair, but does not include building materials or supplies intended for use in such construction, alteration or repair, unless such materials or supplies are within an enclosed building on the premises.

SUBSTANTIAL DAMAGE: Damage of any origin sustained by a structure whereby the cost of restoring the structure to pre-damaged condition would equal or exceed fifty percent (50%) of the market value of the structure before the damage occurred.

SUBSTANTIAL IMPROVEMENT: Any reconstruction, rehabilitation, addition or other improvement of a structure, the cost of which equals or exceeds fifty percent (50%) of the market value of the structure before "start of construction" of the improvement. This term includes structures which have incurred "substantial damage" regardless of the actual repair work performed. The term does not, however, include either:

1. Any project for improvement of a structure to correct existing violations of State or local health, sanitary or safety code specifications that have been identified by the local Code Enforcement Official and which are the minimum necessary to assure safe living conditions, or
2. Any alteration of a "historic structure" provided that the alteration will not preclude the structure's continued designation as a "historic structure".

VARIANCE: A grant of relief by the community from the terms of a floodplain management regulation. Flood insurance requirements remain in place for any varied use or structure and cannot be varied by the community.

VIOLATION: The failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certifications or other evidence of compliance required by this Chapter is presumed to be in violation until such time as that documentation is provided.

WATER SURFACE ELEVATION: The height in relation to the National Geodetic Vertical Datum (NGVD) of 1929 (or other datum where specified) of floods of various magnitudes

and frequencies in the floodplain. (Ord. No. 819 Art. 8, 4-12-05)

ARTICLE IX. ADMINISTRATION AND ENFORCEMENT

SECTION 415.300: DUTIES OF THE FLOODPLAIN ADMINISTRATOR

Duties of the Building Inspector designated as the Floodplain Administrator in the above-referenced ordinance.

1. Understanding the regulations governing the floodplain.
2. Reviewing the flood development permit applications for development.
3. Conducting inspections.
4. Taking enforcement actions when necessary.
5. Interacting in variance and appeal processes.
6. Keeping records of all floodplain development.
7. Collecting fees.
8. Investigating complaints of violations.
9. Maintaining and updating administrative forms.
10. Coordinating map appeals and revisions.
11. Maintaining floodplain maps and flood data.
12. Disseminating floodplain management information. (CC 1984 §6.640; Ord. No. 743 §I, 8-14-00; Ord. No. 824 §I, 4-12-05)

SECTION 415.310: FLOODPLAIN DEVELOPMENT PERMITTING SYSTEM

A. Submittal Of Floodplain Development Permit Application.

1. Permits shall be submitted to City Clerk with an application fee of one hundred dollars (\$100.00) which shall cover both the application fee and the floodplain development fee.
2. *Submittal of floodplain development permit application.*
 - a. Permit shall be submitted to the City Clerk on either the floodplain application checklist form which is on file in the City offices or a substantially similar document with the following documents:

- (1) Plans and blueprints which must show the following:
 - (a) Existing and proposed topographic information, including spot elevations.
 - (b) Boundaries of the floodway and the floodplain.
 - (c) Building elevations for all structures showing the level of the base flood elevation (BFE).
 - (d) Proposed obstructions in the floodway.
 - (e) Professional registered architect, engineer or land surveyor seal, if prepared by same.
 - (f) Illustration of all proposed development.
 - (g) Other considerations:
 - (i) Anchoring requirements.
 - (ii) Construction materials and methods.
 - (iii) Utilities.
 - (iv) Subdivisions.
 - (v) Encroachments.
 - (vi) Elevation of the lowest floor.
 - (vii) Floodways.
- (2) The following technical documents:
 - (a) Elevation/floodproofing certificates.
 - (i) NFIP elevation certificate; provides a record of the as-built elevation of the lowest floor.
 - (ii) NFIP floodproofing certificate; provides a record of the height of floodproofing.
 - (b) Ensure all necessary technical documents are included and property certified.
 - (c) Four (4) conditions that necessitate the filing of certified documentation:
 - (i) *Floodway encroachment/"no-rise" certificate*. If any or part of the proposed project is to be located in a designated floodway, the applicant must submit engineering documentation demonstrating

that the proposed encroachment would not result in any increase in base flood heights. There is no form or special format for a "no-rise" certificate. It may be a written statement, supported by hydraulic computations, signed by a registered professional engineer who certifies that the development will result in no increase in flood heights.

(ii) *Watertight floodproofing.* In the event a non-residential structure is to be floodproofed according to the NFIP standards, the applicant must submit a statement or floodproofing certificate from a registered professional engineer or architect certifying that the design and methods of construction meet these standards. Note: To receive a flood insurance rate based on 100-year flood protection, the non-residential structure must be dry-floodproofed to an elevation at least one (1) foot above the base flood elevation to be rated at the base flood elevation rate (i.e. one (1) foot of freeboard).

(3) Any additional permits and reviews required by the Building Inspector or City Engineer.

b. There shall be an application fee of one hundred dollars (\$100.00) to accompany the permit.

c. The permits and accompanied documents must be properly executed and completely filled in prior to any action on the application.

B. The Building Inspector shall review the application for completeness and compliance with the technical requirements in accordance with the standard application/checklist attached.

C. Review of engineering documents shall be made by City Engineer in particular as to meeting engineering documents linked to NFIP requirements are hydrologic and hydraulic, loading calculation and methods of construction relative to floodproofing, alternative designs for openings below lowest floor, and design and methods of construction for breakaways exceeding SOP loading resistance of twenty (20) pounds per square foot. The City Engineer shall review and approve or furnish within thirty (30) days of receipt.

D. Approval or denial of floodplain development permit application shall proceed as set forth in Chapter 405 of the Municipal Code of the City of New Haven, Missouri. (CC 1984 §6.650; Ord. No. 743 §II, 8-14-00; Ord. No. 824 §II, 4-12-05)

SECTION 415.320: INSPECTION PROCESS

A. *Inspection One.* The Building Inspector shall, within fifteen (15) days of the issuance of the permit, verify the site is consistent with ground conditions shown on plans and location of floodplain and floodway boundaries. The Building Inspector shall fill out a form similar to the sample checklist attached hereto. Any inconsistencies shall be noted on the checklist. A copy of the checklist shall be sent to the permit holder. In the event the ground inspection is inconsistent with proposed plans, the Building Inspector shall notify the permit holder in writing to cease until the inconsistency is eliminated. The inspector shall make the inspection within fifteen (15) days of notification.

- B. *Inspection Two.* The Building Inspector shall inspect the building site just prior to placement of the lowest floor of the structure. The permit holder is obligated to notify the Building Inspector just prior to placement of the lowest floor. The Building Inspector shall make the inspection to verify the type of foundation, height of floor is as per plans submitted. The Building Inspector shall fill out a form similar to the sample checklist on file in the City offices. Any inconsistencies shall be noted on the checklist. A copy of the checklist shall be sent to the permit holder. In the event the ground inspection is inconsistent with proposed plans, the Building Inspector shall notify the permit holder in writing to cease until the inconsistency is eliminated. The inspector shall make the inspection within three (3) days of notification.
- C. *Inspection Three.* The Building Inspector shall inspect the building site near completion of the building. The permit holder is obligated to notify the Building Inspector just prior to completion to determine whether placement of fill (if any) meets standards, enclosures below lowest floor have adequate number of openings and are adequately sized, breakaway walls, etc. The Building Inspector shall fill out a form similar to the sample checklist on file in the City offices. Any inconsistencies shall be noted on the checklist. A copy of the checklist shall be sent to the permit holder. In the event the ground inspection is inconsistent with proposed plans, the Building Inspector shall notify the permit holder in writing to cease until the inconsistency is eliminated. The inspector shall make the inspection within three (3) days of notification.
- D. *Damage Assessment.* In the event of a flood of major proportions which is called a disaster, the following damage assessment will be utilized:
1. The Floodplain Manager will proceed as follows:
 - a. Make a list of damaged facilities;
 - b. Inspect each facility for extent of damages;
 - c. Make a detailed list of damage, such as foundations, basement floors, walls, cabinets, built-in appliances, furnaces, air-conditioners, roofs and any other damage that can be determined;
 - d. Attempt to ascertain a total damage cost for each facility;
 - e. Request the assessed value of each facility or structure from the County Assessor;
 - f. Make a determination by comparing cost of repair or replacement to Assessor's value as to whether the facility is substantially damaged;
 - g. Use the permit procedures for all applications for repair or constructions.
- E. *Additional And Final Inspections.* There shall be an inspection made upon notification by permit holder after notification by Building Inspector of an inconsistency. There shall further be a final inspection upon notification by permit holder of completion to verify consistency to plans submitted. The Building Inspector shall, after each inspection for an inconsistency, note on the inspection checklist the inconsistency found, how the inconsistency was corrected and when. The final inspection if satisfactory shall be noted on

the permit. (CC 1984 §6.660; Ord. No. 743 §III, 8-14-00; Ord. No. 824 §III, 4-12-05)

SECTION 415.330: ENFORCEMENT ACTIONS

Enforcement of a violation shall be as set forth in Chapter 405 of the Municipal Code of the City of New Haven, Missouri. (CC 1984 §6.670; Ord. No. 743 §IV, 8-14-00; Ord. No. 824 §IV, 4-12-05)

SECTION 415.340: VARIANCES

Parties may make a request for variances in this administrative process in the manner set forth in Chapter 405 of the Municipal Code of the City of New Haven, Missouri. (CC 1984 §6.680; Ord. No. 743 §V, 8-14-00; Ord. No. 824 §V, 4-12-05)

SECTION 415.350: RECORD KEEPING SYSTEM

The records of the Building Inspector shall be kept in the offices of the City Clerk of the City of New Haven, Missouri. (CC 1984 §6.690; Ord. No. 743 §VI, 8-14-00)

SECTION 415.360: MAP APPEALS AND REVISIONS

The Building Inspector shall insure that all amendments and modifications of the floodplain maps shall be promptly filed with the floodplain map and adequate copies are kept at City Hall for use of the public. The City Clerk shall prepare for the Floodplain Manager a biennial report to FEMA all changes in the floodplain which shall be signed by the Building Inspector as Floodplain Manager. (CC 1984 §6.691; Ord. No. 743 §VII, 8-14-00; Ord. No. 824 §VII, 4-12-05)